



LT-S14 S Series Sightseeing Bus



LT-S23



LT-S11

LT-S8

LVTONG [®]

Address: Hexi Industry Park, Zhengteng Industry Zone, Hongmei, Dongguan City, Guangdong Province, China.

Tel: +86-769-22773916 Fax: +86-769-88435828 E-Mail: overseas@lvtong.com.cn

Http://en.lvtong.com.cn Http://www.lvtong.en.alibaba.com Http://lvtong.en.made-in-china.com

Model:	LT-S23	LT-S14	LT-S11	LT-S8
Controller	US made Curtis controller	US made Curtis controller	US made Curtis controller	US made Curtis controller
Battery	Trojan/maintenance free battery	Trojan/maintenance free battery	Trojan/maintenance free battery	Trojan/maintenance free battery
Motor	72V/9KW	72V/6.3KW	72V/6.3KW	48V/4KW
Charger	72V/30A	72V/25A	72V/25A	48V/25A
Charging Time	Less than 12 hours (discharging rate 80%)			
Glass	Sandwich glass			
Seat	leather			
Sun Roof	PP Vacuum forming			
Floor	Antiskid rubber floor			
Rear Mirror	Handoperated, both side			
Steering	Dual automotive-style strut and self-adjust rack-and pinion steering			
Dc/light/signal	Front light, turning light, fog light, rear light, horn, Buzzer			
Body	Front body adopts "PP" alloy automobile special engineering material The driving box adopts fiber glass material			
Dash Board	Fiberglass dash board, Voltage Indicator 48V, Switch Head Lights, Switch - Indicators Right/Left, key switch, Switch - Forward/Reverse.			
Braking System	Front disc and rear drum, four-wheel hydraulic brake+hand brake			
Front Axle And Suspension	Independent suspension, helical spring +cylinder hydraulic shock absorption			
Rear Axle And Suspension	Integral type transaxle, gear ratio 12.49:1, semi-independent transaxle, spring, cylinder hydraulic shock absorption	Integral type transaxle, gear ratio 12.31:1, semi-independent transaxle, leaf spring		
Tire Diameter	535mm	535mm	535mm	535mm
Length*width*height	5750*1790*2240mm	4960*1480*1980mm	4590*1480*1980mm	3860*1480*1980mm
Loading Passenger	23	14	11	8
Max Speed Km/h	25-30 km/h	25-30 km/h	28-30 km/h	30-40 km/h
Mileage/km	85-100km (flat road)	80-100km (flat road)	80-100km (flat road)	80-100km (flat road)
Max Climbing Ability	5%	20%	20%	20%
Mini Turning Radium (M)	≤6.4m	≤5.6m	≤5.5m	≤4m
Mini Ground Clearance	250mm	180mm	180mm	180mm
Wheel Base	Front 1515/back 1595mm	Front 1180/back 1200mm	Front 1190/back 1210mm	Front 1190/back 1210mm
Braking Distance	6M	4M	3.5M	3.2M